

Super Storm1500B RGBW

TECHNICAL INFORMATION

Optics

600pcs 1.2W white & 1500W IP65 600pcs 1W RGB LEDs :Light source
LEDs
LM 70,000 :Luminous
*hours 20,000 :LEDs expected lifetime
degrees fixed 120 :Lens options

Features

120° / 0° :Tilt/Pan
300W) segment pixel modes can safely be used as wash-12 :LED Panel
(brightness

Electrical

240V 50/60 Hz — 200 :AC Power
W 1500 :Maximum power consumption
5A :Typical current consumption
5A :Peak current consumption

Programming and Control

USITT DMX512 A :Protocol
Auto Mode ,Slave/Master ,Standalone :Setting and addressing
1/4/7/11/12/24/48/55/70 :DMX channels

Physical

;Weight 9.5 Kg ,x 313 x 123mm 490 :(L x H x W) Dimensions
casting Aluminum-Die :Material
Tempered glass front :Lens

Installation

any :Orientation
Omega Clamp) or hanging (included) Floor stand :Rigging possibilities
(included
Bottom mount for Safety wire :Safety features
casting Aluminum-Die :Material
Tempered glass front :Lens

Thermal

(104°F – 14°) 40°C+ to 10°– :Operating ,Temperature range

90% :(.max) Humidity

Passive :Safety features

Conforms to

Certifications CE and RoHS

Included Items

eyebolt & A sweet Safety Cable

A power Cord

User Manual

Fixtures and Accessories

600pcs 1.2W white LEDs & 600pcs 1W RGB LEDs Super bright output via

;patent of Intella System Ltd *unique design & own ,Innovative technology

;auto mode operating mode ,slave/master ,Standalone

random strobe + in strobe programs–Intense built

(max 300W brightness) segment pixel modes can safely be used as wash–12

in over heat protection temperature sensor to extend the lamp life–Built

bit dimmer–16 & Variable electronic strobe

User adjustable flash rate of 0–30 flashes per second

Flash duration can be set from 0–650ms in DMX mode

7000Hz LED scan rate

button easy to use LCD control panel menu–4

Output/pin DMX Input–5 & pin–3

Out connectors/PowerCon compatible AC power In